



# FJD WIFI CAMERA



# REAL-TIME ACCESS TO OPERATIONAL STATUS

- Quick multi-angle installation without drilling, and multi-angle adjustment is supported.
- Dual cameras are supported to connect control terminal, which can be switched anytime (customized 4-camera connection).
- Automatic sensing for light intensity and infrared night vision support all-weather operations.
- Real-time access to the operational status of attachments and the entire vehicle.
- Anti-flicker, dual code stream, password protection.
- Ingress Protection IP65.
- Auto-connect after power outage and restart, no repeated match.
- Multi-angle installation with real-time monitoring lead to operation safety.

## 1080P

HD

## 150 Mbps

Max transmission rate

## 20 m

Max transmission distance



## QUICK SPECS

Dimension	88*102*128 mm
Power Cord	7 m
Product Weight	370 g
Transmission Distance	20 m
Channel bandwidth	20 MHz

Frequency Range	2.4 GHz ~ 2.4835 GHz
Input Power	DC 12 V, 1 A
Working Temperature	-20°C ~ 60°C
Storage Temperature	-30°C ~ 60°C
Infrared Radiation Range	10 m

Free Quote: [sales.global@fjdynamics.com](mailto:sales.global@fjdynamics.com)

Address: 15 SCOTTS ROAD #03-12, SINGAPORE

[FJDynamics.com](http://FJDynamics.com) 🔍



### CREATE FOR A BETTER WORLD

Copyright © 2022 FJDynamics. All rights reserved.